

Additional Products



Idler Wheel Rollers



Sprockets



Chain Tensioners



Chain Idlers



Torque Limiter Clutches



Articulating Hitches



Bearing Protectors



Friction Drive Rollers




Shakers



CNH Enhancements



Steel Pillow Blocks



TEROG MANUFACTURING



Terog Manufacturing builds quality Black Ace® parts for a wide variety of original equipment, as well as a large selection of replacement parts. Family-owned and -operated since 1971, Terog Manufacturing is a specialist in improving equipment performance and profitability.



blackaceparts.com 387 Atlantic Ave. | P.O. Box 587 | Stephen, MN 56757 218.478.3395 | 800.423.3918

ARTICULATING IMPLEMENT HITCHES

The world's strongest articulating implement hitch creates a vital union between your tractor and implement. These heavy-duty hitches are now made from a hardened steel forging, making them even stronger than before. The Bull-Pull increases drawbar life while eliminating backlash, for precise control. Bull-Pull hitches are built for heavy loads and are easy to install, making them an excellent improvement to a standard pintle hitch.

STANDARD MOUNT









The vital union of your tractor and implement gets the attention it deserves.

- Eliminates backlash for precise control
- Heavy-duty for heavy loads
- New hardened forged steel body, making it even stronger than austempered ductile iron
- Easy installation
- Increases the life of drawbars and drawpins
- Eliminates implement "slam", reducing shock loads on tractor and implement
- Available in categories 2, 3, 4 & 5
- Ability to change from category 3 to 4 in seconds



	PART NUMBER	DRAW PIN SIZE	BALL HOUSING DIAMETER	RECEIVER WIDTH	DRAW PIN TO HOLE MTG	OVERALL LENGTH	HEIGHT (FOR DRAWBAR STRAP)	BOLT HOLE SIZE	BOLT HOLE DISTANCE	# OF BOLT HOLES IN RECEIVER	RECEIVER HEIGHT	HOLE CENTER TO BACK RECEIVER	BALL HOUSING THICKNESS	WEIGHT
	BPF-CAT 3	1-1/4"	5-1/2"	4"	7-1/2"	11"	2-3/4"	1" BOLT	2-1/4"	2	4-1/2"	1-1/4"	2"	31 LBS.
	BPF-CAT 4	1-1/2" OR 2"	5-1/2"	4"	7-1/4"	11"	2-3/4"	1" BOLT	2-1/4"	2	4-1/2"	1-1/4"	2"	31 LBS.
	BPF-CAT 4Z	1-1/2" OR 2"	6-3/8"	4"	7-1/2"	11-3/8"	2-3/4"	1" BOLT	2-1/4"	3	6-3/4"	1-1/8"	2"	39 LBS.
	BPF-CAT 4ZW	1-1/2" OR 2"	5-1/2"	4"	7"	11"	2-3/4"	1-1/4" BOLT	4"	2	6-3/4"	1-1/4"	2"	39 LBS.
	BPF-CAT 4ZCH	1-1/2" OR 2"	6-3/8"	4-3/4"	7-1/2"	11-3/8"	2-3/4"	1-5/8" BOLT	3"	2	6-3/4"	1-1/4"	2"	40 LBS.
	BPF-CAT 4B	1-1/2" OR 2"	5-1/2"	6"	7"	11"	2-3/4"	1" BOLT	2"	3	6-3/4"	1-1/4"	2"	37 LBS.
	BPF-CAT 4CH	1-1/2" OR 2"	5-1/2"	5"	6-1/4"	11"	2-3/4"	1-5/8" BOLT	N/A	1	4-1/2"	2"	2"	32 LBS.
	BPF-CAT 4BW	1-1/2" OR 2"	5-1/2"	4"	7-1/4"	11"	2-3/4"	1" BOLT	3"	2	4-1/2"	1-1/4"	2"	31 LBS.


Standard Mount Continued...



	BPF-CAT 4KU	1-1/2" OR 2"	5-1/2"	4"	7"	11"	2-3/4"	2" PIN	N/A	1	4-1/2"	1-3/8"	2"	30 LBS.
	BPF-CAT 4K	1-1/2" OR 2"	5-1/2"	4"	7-1/4"	11"	2-3/4"	27MM BOLT	2-1/4"	2	4-1/2"	1-1/4"	2"	31 LBS.
	BPF-CAT 4S	1-1/2" OR 2"	5-1/2"	4"	6"	11"	2-3/4"	2-1/2" WEIGH BAR 1" CROSS-PIN	N/A"	1	4-1/2"	2-1/4"	2"	29 LBS.
	BPF-CAT 45	2-3/4"	6-3/8"	4"	7-3/8"	11-3/8"	3-3/8"	1" BOLT	2-1/4"	2	6-3/4"	1-1/8"	2"	38 LBS.
	BP-CAT 45CH	2-3/4"	6-5/8"	5"	6-5/8"	12"	3-3/8"	1-5/8" PIN	N/A	1	4-1/2"	2"	2-3/8"	35 LBS.
	BPF-CAT 5	2-3/4"	6-3/8"	4"	7-3/8"	11-3/8"	3-3/8"	1" BOLT	2-1/4"	3	6-3/4"	1-1/4"	2-3/8"	37 LBS.
	BP-CAT 5B	2-3/4"	6-5/8"	6"	7-3/8"	12"	3-3/8"	1" BOLT	2"	3	6-3/4"	1-1/4"	2-3/8"	45 LBS.
	BPF-CAT 5CH	2-3/4"	6-3/8"	4-3/4"	7"	11-3/8"	3-3/8"	1-5/8" BOLT	3"	2	6-3/4"	1-1/4"	2-3/8"	40 LBS.

HORIZONTAL MOUNT

The same benefits as the standard mount, just a different mounting configuration.

- Austempered ductile iron body
- Available in categories 3, 4 & 5



	PART NUMBER	DRAW PIN SIZE	BALL HOUSING DIAMETER	RECEIVER WIDTH	DRAW PIN TO HOLE MTG	OVERALL LENGTH	HEIGHT (FOR DRAWBAR STRAP)	BOLT HOLE SIZE	BOLT HOLE DISTANCE	# OF BOLT HOLES IN RECEIVER	RECEIVER HEIGHT	HOLE CENTER TO BACK RECEIVER	BALL HOUSING THICKNESS	WEIGHT
	BPF-CAT 4JDF	1-1/2", 2"	5-1/2"	6-1/4"	1" BOLT	2"	2-3/4"	13-1/2"	32 LBS.	3	6-3/4"	1-1/4"	2-3/8"	37 LBS.
	BP-CAT 5JDF	2-1/2", 2-3/4"	6-5/8"	6-3/8"	1" BOLT	2-3/8"	3-3/8"	14"	35 LBS.	3	6-3/4"	1-1/4"	2-3/8"	45 LBS.